

LodgeNet EZAir Wireless Bridge Solution



Even with the proliferation of wireless broadband coverage, many laptop users still prefer a wired connection (or are required by their employers to use one while traveling). The **EZAir bridge helps these guests connect quickly** and easily to your wireless network.



To learn more
1-888-LODGENET (563-4363)
sales@lodgenet.com
www.lodgenet.com

Copyright © 2009 LodgeNet Interactive Corporation. All rights reserved. LodgeNet and the LodgeNet logo are trademarks or registered trademarks of LodgeNet Interactive Corporation. Appearance of hardware may vary from what is shown here. The information contained herein shall be deemed confidential information and at all times will remain proprietary to LodgeNet. This confidential information may not be disclosed to any other person, firm, or entity without the express permission of LodgeNet.

S11650C08-011509

Technical Specifications

Standards Supported

- IEEE 802.11 standard for wireless LAN
- All major networking standards (including IP, IPX)

Environmental

- Operating Temperature (ambient) -10° to 50° C (14° to 122° F)
- Humidity Max. 95% Non-condensing

Power Specifications

- DC Power Supply
 - Input DC 100-240, 50-60 Hz, 2A
 - Output 5V DC 2A converter included

Radio Specifications

- Range
 - Per cell indoors approx. 35 to 75 m (115 to 245 ft)
 - Per cell outdoors up to 100 to 250 m (328 to 820 ft)
- Transmit Power
 - Nominal temp range 14 dBm, 12 min
- Frequency Range
 - 2.4 to 2.4835 GHz, direct sequence spread spectrum
- Number of Channels
 - Most European countries 13 (1 through 13)
 - U.S. and Canada 11 (1 through 11, 3 non-overlapping)
 - France 4 (10 through 13, 1 non-overlapping)
 - Japan 14 (1 through 14)

Specific Features

- Supported bit rates
 - 11 Mbps CCK
 - 5.5 Mbps CCK
 - 1 Mbps DBSK
 - 2 Mbps DQPSK

Data Encryption

- 64-bits WEP encryption
- 128-bits WEP encryption

Utility Management

- Web management and TFTP firmware upgrade